



**pQKD** is a groundbreaking cybersecurity product designed by Quantum Blockchains, Inc. Its chief objective is to expedite the transition towards quantum-resistant cryptographic systems. This is accomplished by meticulously simulating QKD protocols in accordance with the global communication standards established for QKD technology by ETSI.

For its operation, pQKD does not rely on dedicated fiber optic links, but rather utilizes an out-of-band network channel for the distribution of cryptographic keys. This distribution is safeguarded by the Kyber key encapsulation mechanism (KEM), a post-quantum method engineered to withstand cryptanalytic attacks from potent future quantum computers. Kyber is projected to be incorporated into forthcoming NIST standards, ensuring its resilience and reliability in the cybersecurity landscape.

pQKD utilizes a genuine on-chip Quantum Random Number Generator (QRNG) supplied by the industry leader, ID Quantique. The QRNG operates independently of the QKD emulation function, serving as a high-grade local source of entropy for any cryptographic application. This integral feature further strengthens the robustness and versatility of the pQKD system in the field of advanced cybersecurity.

pQKD is highly versatile, capable of interfacing with **any network-layer encryption device** that supports key exchange using ETSI QKD protocols. Furthermore, it's compatible with various hardware and software solutions such as VPN applications and appliances. Broadly speaking, pQKD provides secure key exchange for any quantum-resistant systems. While it doesn't assure the physical security provided by true QKD devices, it does guarantee a level of security that is at least on par with that of post-quantum key distribution mechanisms.

pQKD also offers functionality **as a straightforward encryptor** for network communication applications. In this capacity, it employs highly secure, long-key AES algorithms and the provably secure OTP (one-time pad) methods, delivering enhanced protection in a user-friendly package.

Due to a number of innovations incorporated in the device design it is the subject of the company's **patent application titled "A method and a device for encryption key distribution and communication".** 

## **Device specification**

Post-Quantum Key Distribution - pQKD

QKD (Quantum Key Distribution) emulator with QRNG (Quantum Random Number Generator)

## **Minimum setup**

Two devices ("Alice" and "Bob" pair).

## **Physical form**

Stand alone casing with rack mounted option Dimensions (LWH): 90mm \* 65mm \* 33mm.

#### **Interfaces**

2 \* LAN RJ-45 ports: Simulated Quantum Channel, Service/Data channel.

## **Power Supply**

Via USB-C connector or 19" rack-mounted case connector: 5V, Max Current 2A.

Rack-mounted version: standard AC 110-230V

power supply.

#### **Control elements**

Reset button, Shutdown button.

## **Diagnostic**

LEDs: State, QKD active, QRNG active.

#### **Protocols**

QKD ETSI – 004, ETSI – 014. QRNG API (proprietary Rest API) via HTTPS.

## **Cryptographic algorithms**

Post-Quantum KYBER Key Encapsulation mechanism.

AES with key lengths: 128,256,512,1024, 2048 AES modes of operation: : GCM256, CBC256,

ECB from 256 to 4096.

## **External encryptors**

OTP (One-Time-Pad) or AES devices. Tested with Adva, PacketLight, Thales, FortiGate and Juniper devices.

Tested with VPN systems (WireGuard, OpenVPN, generic).

## **Management interfaces**

Comprehensive Web Interface for interactive setup and configuration.

SNMP protocol (with v1,v2 and v3 authentication).

# **Quantum Random Number Generator**

Quantis IDQ6MC1 by ID Quantique.

## **Availability**

#### **Availability:**

Fully-functional pre-production (CE certified) versions are presently in the shipping phase. Both compact and 1U rack-mounted versions are available.

Certification for fully-secured versions is in progress.



